

BlueTruckMaster®

A PORTABLE TANK FOR DISTRIBUTION
AND TRANSPORT OF AdBlue®

Kingspan

TITAN®

▶ SAFETY TRANSPORT OF AdBlue®

BlueTruckMaster®

EASY TRANSPORTING AND REFUELING
OF AdBlue® ANYWHERE

SAFETY, ACHIEVED BY:

- Unique design of the tank means that it can be easily secured with straps to the vehicle.
- Integrated baffle reduces liquid surge during transport.
- Lockable cover prevents the contents of the tank and equipment from unauthorised access.

CONVENIENCE:

- Fully integrated solution allows for immediate use.
- Automatic nozzle prevents overflow from the vehicle tank.
- The possibility of delivering AdBlue® to the place where it is required.
- Optional range of DC and AC powered pumps with varied flow rates to suit individual needs.

DEPENDABILITY, GUARANTEED BY:

- 5-year warranty for leak tightness of the plastic tank and 2-year warranty for equipment.
- Post-warranty service.
- Manufactured and quality controlled according to ISO 9001:2008 (cert. no FM 57348).
- Highest quality components engineered for long term use with AdBlue®.

STANDARD EQUIPMENT

- Translucent PE tank with integrated baffle.
- Lockable cover.
- Suction line with mesh filter that guarantees purity of pumped liquid.*
- Gas springs.
- Self-priming 12 V DC pump.
- 4 m flexible distribution hose with automatic nozzle.
- Automatic over pressure and vacuum relief valve.
- Offset threaded filling point.

OPTIONAL EQUIPMENT

- Self-priming 24 V DC pump.
- Self-priming 230 V AC pump.
- Digital flow meter for monitoring the amount of liquid pumped.
- Battery-powered LED lamp.
- Lifting shackles.
- Manual nozzle.

* Refers only to 900 l tank.

AVAILABLE CAPACITIES AND DIMENSIONS



PRODUCT CODE
OTM00200WH**

Capacity	200 l
Length	1.18 m
Width	0.86 m
Height	0.50 m



PRODUCT CODE
OTM00430WH**

Capacity	430 l
Length	1.18 m
Width	0.86 m
Height	0.91 m



PRODUCT CODE
OTM00900WH**

Capacity	900 l
Length	1.41 m
Width	1.05 m
Height	1.21 m



Flow meter



Distribution system

The exact hues of the colours presented in the flyers may differ, depending on the quality of print.

Product specifications may be slightly modified; to obtain an up-to-date equipment specification, contact the office or the nearest distributor.

Product dimensions may vary within +/- 1%.

* Code ending may vary depending on equipment.

The warranty applies to the product used in a manner consistent with manufacturer's recommendations.

Distributor:

